

LiveAction® LiveNA Appliance



Basic System Configuration

- 2U server chassis
- 2x Intel® Xeon® 6230 Gold, 2.1 GHz CPU, 20C/40T
- 384 GB RAM
- 23 TB SSD SATA read intensive 6Gbps drives
- NVIDIA Tesla V100S 32 G Passive GPU
- Two built-in 10 GbE and two built-in 1 GbE ports
- Dual, hot-plug, redundant power supplies (1+1), 2400 W

Management Interface (iDRAC)

Supports remote power control, re-installation, BIOS access, and system management.

Environmental

- Operating temperature: 10° to 35° C (50° to 95° F)
- Non-operating temperature: -40° to 65° C (-40° to 149° F)
- Operating relative humidity: 10% to 80% (non-condensing)
- Non-operating relative humidity: 5% to 95% (non-condensing)
- 9000 BTU/Hour

Power and System Input Requirements

- 2400 W redundant power supply
- AC input voltage: 100-240 VAC
- Rated input current: 16A
- Rated input frequency: 50–60 Hz

Dimensions and Weight

- Rack-mount 2U appliance
- 3.4" h x 17.1" w x 29.0" d (8.7 cm x 43.4 cm x 73.8 cm)
- 63.0 lbs (28.6 kg)

Warranty

- On-site warranty service
- Available with up to five year warranty from date of purchase

Software Packages

- Pre-loaded, tested, and fully integrated LiveNA Engine operating system perpetual license
- Ubuntu Linux
- Web-based configuration and management utility

Learn more about LiveNA Appliance

Email sales@liveaction.com or call +1.888.881.1116. Or visit us online at: <https://www.liveaction.com/products/livena-network-analytics/>