

LiveAction® LiveNX Appliance

Basic System Configuration

- 1U server chassis
- 2x Intel® Xeon® 5218 Gold, 2.3 GHz CPU, 16C/32T
- 768 GB RAM
- 32 TB SATA storage, RAID 10, with 16 TB available for storage
- Two built-in 1 GbE BASE-T ports
- Two built-in 10 GbE BASE-T ports
- Dual, hot-plug, redundant power supply (1+1), 750 W

Management Interface (iDRAC)

Supports remote power control, re-installation, BIOS access, and system management.

Environmental

- Operating temperature: 10° to 35° C (50° to 95° F)
- Non-operating temperature: -40° to 65° C (-40° to 149° F)
- Operating relative humidity: 10% to 80% (non-condensing)
- Non-operating relative humidity: 5% to 95% (non-condensing)
- 2891 BTU/Hour

Power and System Input Requirements

- 750 W redundant power supply
- AC input voltage: 100-240 VAC
- Rated input current: 10 -5A
- Rated input frequency: 50–60 Hz

Dimensions and Weight

- Rack-mount 1U appliance
- 1.7" h x 19.0" w x 31.8" d (4.3 cm x 48.2 cm x 80.9 cm)
- 48.3 lbs (21.9 kg)

Warranty

- On-site warranty service
- Available with up to five year warranty from date of purchase

Software Packages

- Pre-loaded, tested, and fully integrated LiveNX Engine operating system perpetual license
- Ubuntu Linux
- Web-based configuration and management utility

Learn more about LiveNX Appliance

Email sales@liveaction.com or call +1.888.881.1116. Or visit us online at: <https://www.liveaction.com/products/LiveNX-network-monitoring-software/>