

LiveNX 6210 Appliance

TECHNICAL SPECIFICATIONS

Basic System Configuration

- 2U server chassis
- 2x AMD EPYC 9354 3.25GHz, 16C/32T
- 1 TB RAM
- 240 TB SAS storage, RAID 6
- 2x built-in 1 GbE BASE-T ports
- 2x built-in 10 GbE BASE-T ports
- Dual, hot-plug, redundant power supplies (1+1), 2400 W

Management Interface (iDRAC)

- Supports remote power control, re-installation, BIOS access, and system management.

Environmental

- Operating temperature: 10° to 35° C (50° to 95° F)
- Non-operating temperature: -40° to 65° C (-40° to 149° F)
- Operating relative humidity: 10% to 80% (non-condensing)
- Non-operating relative humidity: 5% to 95% (non-condensing)
- 2400 W redundant power supply
- AC input voltage: 100-240 VAC
- Rated input current: 12A
- Rated input frequency: 50–60 Hz

Dimensions and Weight

- Rack-mount 2U appliance
- Height – 86.8 mm (3.41 inches)
- Width – 482 mm (18.97 inches)
- Depth – 772.13 mm (30.39 inches) with bezel

Warranty

- On-site warranty service
- Available with up to five-year warranty from date of purchase

Software Packages

- Pre-loaded, tested, and fully integrated LiveNX Engine operating system and subscription
- Ubuntu Linux
- Web-based configuration and management utility

Learn more about LiveNX Appliance

Email sales@liveaction.com or call +1.888.881.1116.

Or visit us online at: [LiveNX | Enterprise Network Monitoring Software - LiveAction](#)